

LEDOLUX

POLAND

Intelligent LED luminaire TANK DOB 2 HT

2 YEARS
WARRANTY



ELECTRICAL CHARACTERISTICS

Driver	Ledolux DOB
Power supply	205-255V~ 50/60Hz
Power factor (cosφ)	≥0.95
Control options	1-10V
Protection class	I

LUMINOUS CHARACTERISTICS

Light source	Lumileds LEDs
Luminaire efficacy	130lm/W
Beam angle	110D
Colour temperature	4000K / 5000K
CRI	>80


GENERAL CHARACTERISTICS

Type of housing	Aluminium
Type of diffuser	Tempered glass
Protection degree IP	IP66
Impact resistance degree IK08 IK	
Operating temperature	-35°C ÷ +90°C
Lifetime (L90B10)	>60 000h
Installation	Surface-mounted, suspended ⁽¹⁾
Mounting height	2-10m
Application	Production halls, warehouses and rooms in metallurgy
Certificates	CE, RoHS

(1) requires an extra chargeable accessory


Power	Luminous flux (measured on the luminaire)	Rated current	Inrush current	Weight	Dimensions
35W	4 550lm	0.16A	~0.20A	1.7kg	L610xW74xH100mm
70W	9 100lm	0.33A	~0.40A	3.0kg	L1200xW74xH100mm
140W	18 200lm	0.67A	~0.83A	6.5kg	L1200xW160xH100mm
210W	27 300lm	1.01A	~1.30A	10kg	L1200xW250xH100mm

PHOTOMETRY



110D

TECHNICAL DRAWING



ACCESSORIES

- Adjustable mounting bracket**(standard accessories)
Mounting bracket for surface mounting of the luminaire with an adjustable position along the luminaire and the angle of inclination of the luminaires -90° ÷ +90°.
- Mounting cables**
For hanging the luminaire.